



DC BRUSHLESS MOTOR
JIB SERIES
Ø 38x23 mm



- Construction:
 - Plastic base
 - Metal rotor
- Operating temperature: Ball bearing -30 °C to +75 °C
- Insulation Resistance: 10 meg Ohm min. at 500 VDC (between frame and terminal)
- Dielectric Strength: 5 mA max. at 500 VAC 60Hz one minute (between frame and terminal)
- Weight: 60 grams

Model No.	Bearing	Rated Voltage Range	Operating Voltage Range	Rated Current	Rated Input Power	Speed
		VDC	V	A	W	R.P.M.
JIB0412LL	Ball	12	10.2~13.8	0.11	1.32	4900
JIB0412LM	Ball	12	10.2~13.8	0.12	1.44	5700
JIB0412LH	Ball	12	10.2~13.8	0.14	1.68	6400
JIB0412RL	Ball	12	10.2~13.8	0.11	1.32	4900
JIB0412RM	Ball	12	10.2~13.8	0.12	1.44	5700
JIB0412RH	Ball	12	10.2~13.8	0.14	1.68	6400
JIB0424LL	Ball	24	20.4~27.6	0.11	2.64	4900
JIB0424LM	Ball	24	20.4~27.6	0.12	2.88	5700
JIB0424LH	Ball	24	20.4~27.6	0.13	3.12	6400
JIB0424RL	Ball	24	20.4~27.6	0.11	2.64	4900
JIB0424RM	Ball	24	20.4~27.6	0.12	2.88	5700
JIB0424RH	Ball	24	20.4~27.6	0.13	3.12	6400

Dimensions (mm)

