

ADAPTERS

General Specification:

- Switching mode
- Operating temperature: 0 to 40°C
- Storage temperature: -40 +85°C
- Operating humidity 10%-90% RH non cond.
- Short circuit protection
- Over current protection
- Over voltage protection
- High efficiency & L.P. consumption

YS series

Range: 1-5W



Input:	100-240 VAC		
Frequency:	47-63 Hz		
Dimensions:	46x34x24 mm		
N.W.:	66 gr		
Output voltage (DC):	5V	12V	24V
Output current max:	1A	0.5A	0.25A

Range: 6-18W



Input:	100-240 VAC		
Frequency:	47-63 Hz		
Dimensions:	75x43x26 mm		
N.W.:	135 gr		
Output voltage (DC):	5V	12V	24V
Output current max:	2A	1.25A	0.6A

Range: 20-40W



Input:	100-240 VAC		
Frequency:	47-63 Hz		
Dimensions:	105x45x28 mm		
N.W.:	120 gr		
Output voltage (DC):	5V	12V	24V
Output current max:	5A	3A	1.5A

Range: 25-35W



Input:	100-240 VAC		
Frequency:	47-63 Hz		
Dimensions:	85x55x35 mm		
N.W.:	125 gr		
Output voltage (DC):	5V	12V	24V
Output current max:	3A	2.5A	1.2A

Range: 50-65W



Input:	100-240 VAC		
Frequency:	47-63 Hz		
Dimensions:	116x52x32 mm		
N.W.:	260 gr		
Output voltage (DC):	5V	12V	24V
Output current max:	6A	5A	2.5A

Range: 70-100W



Input:	100-240 VAC		
Frequency:	47-63 Hz		
Dimensions:	116x56x34 mm		
N.W.:	240 gr		
Output voltage (DC):	5V	12V	24V
Output current max:	10A	8A	3A

Range: 72-95W



Input:	100-240 VAC		
Frequency:	47-63 Hz		
Dimensions:	126x51x34 mm		
N.W.:	260 gr		
Output voltage (DC):	5V	12V	24V
Output current max:	8A	6A	3.5A

Range: 5-65W



Input:	100-240 VAC		
Frequency:	47-63 Hz		
AC plug:	Interchangeable		
Output voltage (DC):	On request		
Output current max:	On request		



RoHS

CB



CE

FC

cULus



ISO 9001 CERTIFICATED

ISO 14001 CERTIFICATED

Different Power or DC Output Voltage available on request